

PRODUCT SPECIFICATION**Deltaline® BTR****Black Temporary Removable Patterned Masking Tape**

Deltaline BTR Black is an easy to install, highly durable, completely removable means of providing a temporary cover for permanent roadway delineation. Deltaline BTR is available in a variety of widths and is intended primarily for construction zones when permanent markings are masked out temporarily but will be used in the future.

Composition

Deltaline BTR consists of a layer of anti-skid particles bonded to a patterned surface of specially formulated polymer resins, pigments, fillers and an integrated reinforcing system. The bottom side of Deltaline BTR is coated with a unique pressure sensitive adhesive which has been specifically designed to firmly adhere to properly prepared surfaces and existing pavement markings.

Application

Proper surface preparation is required for satisfactory results. Essentially, the surface must be clean and dry, with a surface temperature of 50°F and rising. Deltaline BTR cannot be successfully applied over loose or caked dirt, gravel, oily residues, road salt residues, or other foreign substances which will interfere with proper bonding. Review manufacturer's application instructions for more detailed information.

Skid Resistance

The surface of Deltaline BTR provides excellent skid resistance. When tested according to the procedures specified in ASTM-E-303, Deltaline BTR exhibits an initial minimum skid resistance value of 45 BPN.

Removal

Deltaline BTR tape is designed to allow removal intact or in large pieces. The use of heat solvents, hydroblasting grinding, or other methods damaging to the road surface or permanent marking is not needed. It may be necessary to use a sharp edge to start the removal of Deltaline BTR, then lift one edge of the tape and pull at a 90° angle to the surface. The temperature should be 40°F or higher. At lower temperatures, Deltaline BTR may be somewhat more difficult to remove and excess breakage may occur.

Important Notice To Buyer:

All statements, technical information and recommendations contained herein are based on tests believed to be reliable. The accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied:

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever in connection therewith.

Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.